

AGRIMAX RT-657 (65 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40
							REC.	ALT.									
320/65 R 16 117 D / 120 A8	RT-657	319	822	366	2466	390	W10	W9 W11	65	605	710	810	900	990	1070	1185	1285
									50	635	745	855	945	1040	1125	1245	1350
									40	660	770	885	980	1080	1165	1290	1400
									30	700	815	935	1040	1140	1230	1365	1480
									10 LT	815	950	1090	1210	1330	1436	1590	1725
									10 HT	700	815	935	1040	1140	1230	1365	1480
320/65 R 18 109 A8 / B	RT-657	319	873	392	2587	410	W10	W9 W11	50	600	695	785	870	950	1030	-	-
									40	600	695	785	870	950	1030	-	-
									30	645	745	840	930	1020	1105	-	-
									10 LT	805	930	1055	1165	1275	1385	-	-
									10 HT	645	745	840	930	1020	1105	-	-
420/65 R 20 135 D / 138 A8	RT-657	418	1054	468	3162	500	W13	W11 W12	65	1025	1200	1375	1530	1680	1810	2010	2180
									50	1080	1260	1445	1605	1765	1905	2110	2290
									40	1110	1300	1490	1655	1820	1960	2175	2360
									30	1180	1385	1585	1760	1935	2085	2310	2510
									10 LT	1375	1610	1845	2050	2255	2430	2695	2925
									10 HT	1180	1385	1585	1760	1935	2085	2310	2510
440/65 R 20 138 D / 141 A8	RT-657	441	1080	479	3240	525	W14L	W13 W15L	65	1110	1300	1490	1655	1820	1960	2175	2360
									50	1170	1365	1565	1740	1910	2060	2285	2480
									40	1215	1420	1625	1805	1985	2140	2370	2575
									30	1280	1495	1715	1905	2095	2255	2500	2715
									10 LT	1490	1745	1995	2220	2440	2630	2915	3165
									10 HT	1280	1495	1715	1905	2095	2255	2500	2715
420/65 R 24 138 D / 141 A8	RT-657	418	1156	519	3468	550	W13	W11 W12	65	1110	1300	1490	1655	1820	1960	2175	2360
									50	1170	1365	1565	1740	1910	2060	2285	2480
									40	1215	1420	1625	1805	1985	2140	2370	2575
									30	1280	1495	1715	1905	2095	2255	2500	2715
									10 LT	1490	1745	1995	2220	2440	2630	2915	3165
									10 HT	1280	1495	1715	1905	2095	2255	2500	2715
440/65 R 24 135 D / 138 A8	RT-657	441	1182	529	3546	575	W14L	W13 W15L	65	1050	1225	1375	1530	1680	1810	2010	2180
									50	1100	1285	1445	1605	1765	1905	2110	2290
									40	1135	1325	1490	1655	1820	1960	2175	2360
									30	1205	1410	1585	1760	1935	2085	2310	2510
									10 LT	1405	1640	1845	2050	2255	2430	2695	2925
									10 HT	1205	1410	1585	1760	1935	2085	2310	2510

AGRIMAX RT-657 (65 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40
							REC.	ALT.									
480/65 R 24 140 D /143 A8	RT-657	479	1234	550	3702	600	W15L	W14L	65	1200	1400	1575	1750	1925	2075	2300	2500
									50	1260	1470	1655	1840	2025	2180	2415	2625
									40	1310	1530	1720	1910	2100	2265	2510	2725
									30	1380	1610	1815	2015	2215	2390	2645	2875
									10 LT	1610	1880	2115	2345	2580	2785	3085	3350
									10 HT	1380	1610	1815	2015	2215	2390	2645	2875
540/65 R 24 146 D /149 A8	RT-657	530	1312	580	3936	625	W16L	W18L	65	1440	1680	1890	2100	2310	2490	2760	3000
									50	1515	1765	1985	2205	2430	2615	2900	3150
									40	1560	1820	2050	2275	2505	2700	2990	3250
									30	1660	1935	2175	2415	2660	2865	3175	3450
									10 LT	1930	2255	2535	2815	3100	3340	3700	4020
									10 HT	1660	1935	2175	2415	2660	2865	3175	3450
440/65 R 28 138 D /141 A8	RT-657	441	1283	580	3849	625	W14L	W13 W15L	65	1135	1325	1490	1655	1820	1960	2175	2360
									50	1195	1390	1565	1740	1910	2060	2285	2480
									40	1240	1445	1625	1805	1985	2140	2370	2575
									30	1305	1525	1715	1905	2095	2255	2500	2715
									10 LT	1520	1775	1995	2220	2440	2630	2915	3165
									10 HT	1305	1525	1715	1905	2095	2255	2500	2715
480/65 R 28 142 D /145 A8	RT-657	479	1335	600	4005	650	W15L	W14L	65	1275	1485	1670	1855	2045	2200	2440	2650
									50	1340	1560	1755	1950	2145	2315	2565	2785
									40	1395	1625	1830	2030	2235	2410	2670	2900
									30	1465	1710	1925	2135	2350	2535	2810	3050
									10 LT	1710	1995	2240	2490	2740	2955	3275	3555
									10 HT	1465	1710	1925	2135	2350	2535	2810	3050
540/65 R 28 149 D /152 A8	RT-657	530	1413	638	4311	675	W16L	W18L	65	1560	1820	2050	2275	2505	2700	2990	3250
									50	1640	1915	2155	2395	2630	2835	3145	3415
									40	1705	1990	2240	2485	2735	2950	3270	3550
									30	1800	2095	2360	2620	2880	3105	3445	3740
									10 LT	2095	2440	2745	3050	3355	3615	4010	4355
									10 HT	1800	2095	2360	2620	2880	3105	3445	3740
600/65 R 28 154 D /157 A8	RT-657	611	1491	670	4500	700	DW 20 B	W18L	65	1800	2100	2365	2625	2890	3115	3450	3750
									50	1895	2210	2485	2760	3035	3275	3625	3940
									40	1980	2310	2600	2890	3180	3425	3795	4125
									30	2075	2420	2720	3025	3325	3585	3970	4315
									10 LT	2415	2815	3170	3520	3870	4175	4625	5025
									10 HT	2075	2420	2720	3025	3325	3585	3970	4315

AGRIMAX RT-657 (65 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40
							REC.	ALT.									
540/65 R 30 150 D /153 A8	RT-657	530	1464	657	4392	700	W16L	W18L	65	1610	1880	2115	2345	2580	2785	3085	3350
									50	1690	1975	2220	2465	2715	2925	3240	3520
									40	1755	2045	2300	2555	2815	3030	3360	3650
									30	1855	2160	2430	2700	2970	3200	3550	3855
									10 LT	2160	2515	2830	3145	3460	3730	4135	4490
									10 HT	1855	2160	2430	2700	2970	3200	3550	3855
600/65 R 30 155 D /158 A8	RT-657	611	1542	690	4610	725	DW 20 B	W18L	65	1860	2170	2445	2715	2985	3220	3565	3875
									50	1955	2280	2565	2850	3135	3380	3745	4070
									40	2040	2380	2680	2975	3275	3530	3910	4250
									30	2145	2500	2810	3125	3435	3705	4105	4460
									10 LT	2495	2910	3275	3640	4005	4315	4780	5195
									10 HT	2145	2500	2810	3125	3435	3705	4105	4460
540/65 R 34 152 D /155 A8	RT-657	530	1566	711	4725	750	W16L	W18L	65	1705	1990	2240	2485	2735	2950	3270	3550
									50	1795	2090	2350	2615	2875	3100	3435	3730
									40	1860	2170	2445	2715	2985	3220	3565	3875
									30	1965	2290	2575	2860	3150	3395	3760	4085
									10 LT	2285	2670	3000	3335	3670	3955	4380	4760
									10 HT	1965	2290	2575	2860	3150	3395	3760	4085
600/65 R 34 157 D /160 A8	RT-657	611	1644	742	4960	775	DW 20 B	W18L	65	1980	2310	2600	2890	3180	3425	3795	4125
									50	2085	2430	2735	3035	3340	3600	3990	4335
									40	2160	2520	2835	3150	3465	3735	4140	4500
									30	2280	2660	2990	3325	3655	3940	4370	4745
									10 LT	2655	3100	3485	3875	4260	4590	5090	5530
									10 HT	2280	2660	2990	3325	3655	3940	4370	4745
540/65 R 38 153 D /156 A8	RT-657	530	1667	758	5000	800	W16L	W18L	65	1755	2045	2300	2555	2815	3030	3360	3650
									50	1845	2150	2420	2685	2955	3185	3530	3835
									40	1920	2240	2520	2800	3080	3320	3680	4000
									30	2020	2355	2650	2940	3235	3490	3865	4200
									10 LT	2350	2745	3085	3430	3770	4065	4505	4895
									10 HT	2020	2355	2650	2940	3235	3490	3865	4200
600/65 R 38 159 D /162 A8	RT-657	611	1745	793	5265	825	DW 20B	W18L	65	2100	2450	2760	3065	3370	3635	4025	4375
									50	2210	2575	2895	3220	3540	3815	4230	4595
									40	2280	2660	2995	3325	3660	3945	4370	4750
									30	2420	2820	3175	3525	3880	4180	4635	5035
									10 LT	2820	3285	3695	4110	4520	4870	5400	5865
									10 HT	2420	2820	3175	3525	3880	4180	4635	5035

AGRIMAX RT-657 (65 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40
							REC.	ALT.		Load capacity (kg / tyre)							
650/65 R 38 163 D /166 A8	RT-657	645	1811	830	5563	875	DW20B	---	65	2340	2730	3075	3415	3755	4050	4485	4875
									50	2460	2870	3230	3585	3945	4250	4715	5120
									40	2545	2970	3340	3710	4085	4400	4880	5300
									30	2695	3145	3535	3930	4320	4660	5165	5610
									10 LT	3140	3660	4120	4575	5035	5425	6015	6535
									10 HT	2695	3145	3535	3930	4320	4660	5165	5610
650/65 R 42 165 D /168 A8	RT-657	645	1913	866	5739	925	DW20B	---	65	2475	2885	3245	3605	3970	4275	4740	5150
									50	2600	3030	3410	3790	4170	4495	4980	5410
									40	2690	3140	3530	3920	4315	4650	5155	5600
									30	2845	3320	3735	4150	4565	4920	5455	5925
									10 LT	3315	3870	4355	4835	5320	5735	6355	6905
									10 HT	2845	3320	3735	4150	4565	4920	5455	5925

SW - On the first Rim of the list.

65/50/40/30 = On Road transport at 65/50/40/30 km/h.

10 LT = Maximum speed 10 km/h. Surface treatment with low torque value.

10 HT = Maximum speed 10 km/h. Field application with high torque value.

For dual mounting use, per each wheel , the 88% of loading indicated for single mounting.

* All tyres conform to ETRTO standards.

S = Single fitment.

SRI = Speed Radius index - value to be used for the calculation of the theoretical tractor speed during European Union homologation and for the interchangeability of different type sizes.