

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
							REC.	ALT.												
Load capacity (kg / tyre)																				
180/95 R 16 105 A8 /B	RT-855	185	760	340	2265		5.5F	---	50	---	430	---	550	---	670	735	790	865	925	---
									40	---	430	---	550	---	670	735	790	865	925	---
									30	---	460	---	585	---	715	785	845	925	990	---
									10	---	505	---	655	---	795	950	1085	1130	1255	1390
210/95 R 16 106 A8 /B (Replaces 7.50 R 16)	RT-855	209	806	360	2415	390	W 6.5	W 6	50	450	515	590	665	745	820	885	950	---	---	---
									40	450	515	590	665	745	820	885	950	---	---	---
									30	480	555	635	715	800	880	950	1020	---	---	---
									10 LT	600	690	795	895	995	1100	1190	1275	---	---	---
									10 HT	480	555	635	715	800	880	950	1020	---	---	---
210/95 R 18 108 A8 /B (Replaces 7.50 R 18)	RT-855	209	855	385	2565	410	W 6.5	W 6	50	470	540	620	700	780	860	930	1000	---	---	---
									40	470	540	620	700	780	860	930	1000	---	---	---
									30	505	580	665	750	835	925	1000	1070	---	---	---
									10 LT	630	725	835	940	1050	1155	1250	1340	---	---	---
									10 HT	505	580	665	750	835	925	1000	1070	---	---	---
210/95 R 20 110 A8 /B (Replaces 8.3 R 20)	RT-855	211	890	404	2661	425	W 7	W 6	50	500	575	660	745	830	915	990	1060	---	---	---
									40	500	575	660	745	830	915	990	1060	---	---	---
									30	535	615	705	795	890	980	1060	1135	---	---	---
									10 LT	670	770	885	1000	1115	1230	1330	1425	---	---	---
									10 HT	535	615	705	795	890	980	1060	1135	---	---	---
250/85 R 20 116 A8 /B (Replaces 9.50 R 20)	RT-855	250	940	424	2820	450	W8	W 7	50	590	675	775	875	975	1075	1165	1250	---	---	---
									40	590	675	775	875	975	1075	1165	1250	---	---	---
									30	630	725	835	940	1050	1155	1250	1340	---	---	---
									10 LT	790	905	1040	1175	1310	1445	1560	1675	---	---	---
									10 HT	630	725	835	940	1050	1155	1250	1340	---	---	---
280/85 R 20 112 A8 /B (Replaces 11.2 R 20)	RT-855	292	984	441	2935	475	W10	W9	50	620	720	820	920	1020	1120	---	---	---	---	---
									40	620	720	820	920	1020	1120	---	---	---	---	---
									30	660	770	880	985	1095	1200	---	---	---	---	---
									10 LT	830	965	1100	1235	1370	1505	---	---	---	---	---
									10 HT	660	770	880	985	1095	1200	---	---	---	---	---
320/85 R 20 119 A8 /B (Replaces 12.4 R 20)	RT-855	329	1052	467	3114	500	W11	W9	50	750	875	995	1120	1240	1360	---	---	---	---	---
									40	750	875	995	1120	1240	1360	---	---	---	---	---
									30	805	935	1070	1200	1330	1460	---	---	---	---	---
									10 LT	1005	1170	1335	1500	1665	1825	---	---	---	---	---
									10 HT	805	935	1070	1200	1330	1460	---	---	---	---	---

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
							REC.	ALT.												
Load capacity (kg / tyre)																				
250/85 R 24 109 A8 /B (Replaces 9.5 R 24)	RT-855	251	1036	472	3087	500	W8	W7 W9	50	570	660	755	845	940	1030	---	---	---	---	---
									40	570	660	755	845	940	1030	---	---	---	---	---
									30	610	710	810	910	1010	1105	---	---	---	---	---
									10 LT	765	890	1015	1140	1265	1385	---	---	---	---	---
									10 HT	610	710	810	910	1010	1105	---	---	---	---	---
280/85 R 24 115 A8 /B (Replaces 11.2 R 24)	RT-855	292	1086	492	3224	525	W10	W9	50	670	780	890	1000	1110	1215	---	---	---	---	---
									40	670	780	890	1000	1110	1215	---	---	---	---	---
									30	720	840	955	1075	1190	1305	---	---	---	---	---
									10 LT	900	1045	1190	1340	1485	1630	---	---	---	---	---
									10 HT	720	840	955	1075	1190	1305	---	---	---	---	---
320/85 R 24 122 A8 /B (Replaces 12.4 R 24)	RT-855	329	1154	518	3424	550	W11	W9 W10	50	825	960	1095	1230	1365	1500	---	---	---	---	---
									40	825	960	1095	1230	1365	1500	---	---	---	---	---
									30	885	1030	1175	1320	1465	1605	---	---	---	---	---
									10 LT	1110	1290	1470	1650	1830	2010	---	---	---	---	---
									10 HT	885	1030	1175	1320	1465	1605	---	---	---	---	---
340/85 R 24 125 A8 /B (Replaces 13.6 R 24)	RT-855	353	1188	531	3540	575	W12	W11	50	910	1060	1205	1355	1505	1650	---	---	---	---	---
									40	910	1060	1205	1355	1505	1650	---	---	---	---	---
									30	975	1135	1295	1455	1615	1770	---	---	---	---	---
									10 LT	1220	1420	1620	1820	2020	2215	---	---	---	---	---
									10 HT	975	1135	1295	1455	1615	1770	---	---	---	---	---
380/85 R 24 131 A8 /B (Replaces 14.9 R 24)	RT-855	380	1256	554	3699	600	W12	W11 W13	50	1075	1250	1425	1600	1775	1950	---	---	---	---	---
									40	1075	1250	1425	1600	1775	1950	---	---	---	---	---
									30	1150	1340	1530	1715	1905	2090	---	---	---	---	---
									10 LT	1440	1675	1910	2145	2380	2615	---	---	---	---	---
									10 HT	1150	1340	1530	1715	1905	2090	---	---	---	---	---
420/85 R 24 137 A8 /B (Replaces 16.9 R 24)	RT-855	438	1324	585	3931	625	W15 L	W14L W13	50	1265	1475	1680	1890	2095	2300	---	---	---	---	---
									40	1265	1475	1680	1890	2095	2300	---	---	---	---	---
									30	1360	1580	1800	2025	2245	2465	---	---	---	---	---
									10 LT	1700	1975	2255	2530	2810	3085	---	---	---	---	---
									10 HT	1360	1580	1800	2025	2245	2465	---	---	---	---	---
250/85 R 28 112 A8 /B (Replaces 9.5 R 28)	RT-855	251	1137	523	3388	550	W8	W7 W9	50	620	720	820	920	1020	1120	---	---	---	---	---
									40	620	720	820	920	1020	1120	---	---	---	---	---
									30	660	770	880	985	1095	1200	---	---	---	---	---
									10 LT	830	965	1100	1235	1370	1505	---	---	---	---	---
									10 HT	660	770	880	985	1095	1200	---	---	---	---	---

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
							REC.	ALT.												
Load capacity (kg / tyre)																				
280/85 R 28 118 A8 /B (Replaces 11.2 R 28)	RT-855	292	1187	542	3542	575	W10	W9	50	730	845	965	1085	1205	1320	---	---	---	---	---
									40	730	845	965	1085	1205	1320	---	---	---	---	---
									30	780	910	1035	1165	1290	1415	---	---	---	---	---
									10 LT	975	1135	1295	1455	1615	1770	---	---	---	---	---
									10 HT	780	910	1035	1165	1290	1415	---	---	---	---	---
320/85 R 28 124 A8 /B (Replaces 12.4 R 28)	RT-855	329	1255	569	3743	600	W11	W9 W10	50	880	1025	1170	1315	1460	1600	---	---	---	---	---
									40	880	1025	1170	1315	1460	1600	---	---	---	---	---
									30	945	1100	1255	1410	1565	1715	---	---	---	---	---
									10 LT	1180	1375	1570	1760	1955	2145	---	---	---	---	---
									10 HT	945	1100	1255	1410	1565	1715	---	---	---	---	---
340/85 R 28 127 A8 /B (Replaces 13.6 R 28)	RT-855	353	1289	582	3841	625	W12	W11	50	965	1120	1280	1435	1595	1750	---	---	---	---	---
									40	965	1120	1280	1435	1595	1750	---	---	---	---	---
									30	1035	1200	1370	1540	1710	1875	---	---	---	---	---
									10 LT	1290	1505	1715	1925	2135	2345	---	---	---	---	---
									10 HT	1035	1200	1370	1540	1710	1875	---	---	---	---	---
380/85 R 28 133 A8 /B (Replaces 14.9 R 28)	RT-855	380	1357	606	4018	650	W12	W11 W13	50	1135	1320	1505	1690	1875	2060	---	---	---	---	---
									40	1135	1320	1505	1690	1875	2060	---	---	---	---	---
									30	1215	1415	1610	1810	2010	2205	---	---	---	---	---
									10 LT	1525	1770	2020	2270	2520	2765	---	---	---	---	---
									10 HT	1215	1415	1610	1810	2010	2205	---	---	---	---	---
420/85 R 28 139 A8 /B (Replaces 16.9 R 28)	RT-855	438	1425	636	4234	675	W15L	W13 W14L	50	1340	1560	1775	1995	2215	2430	---	---	---	---	---
									40	1340	1560	1775	1995	2215	2430	---	---	---	---	---
									30	1435	1670	1905	2140	2375	2605	---	---	---	---	---
									10 LT	1795	2090	2380	2675	2970	3260	---	---	---	---	---
									10 HT	1435	1670	1905	2140	2375	2605	---	---	---	---	---
380/85 R 30 135 A8 /B (Replaces 14.9 R 30)	RT-855	380	1408	629	4151	675	W12	W11 W13	50	1200	1400	1595	1790	1985	2180	---	---	---	---	---
									40	1200	1400	1595	1790	1985	2180	---	---	---	---	---
									30	1285	1495	1705	1915	2125	2335	---	---	---	---	---
									10 LT	1610	1875	2140	2400	2665	2925	---	---	---	---	---
									10 HT	1285	1495	1705	1915	2125	2335	---	---	---	---	---
420/85 R 30 140 A8 /B (Replaces 16.9 R 30)	RT-855	438	1475	661	4393	700	W15L	W13 W14L	50	1375	1600	1825	2050	2275	2500	---	---	---	---	---
									40	1375	1600	1825	2050	2275	2500	---	---	---	---	---
									30	1475	1715	1955	2195	2435	2675	---	---	---	---	---
									10 LT	1845	2145	2450	2750	3050	3350	---	---	---	---	---
									10 HT	1475	1715	1955	2195	2435	2675	---	---	---	---	---

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
							REC.	ALT.												
Load capacity (kg / tyre)																				
460/85 R 30 145 A8 /B (Replaces 18.4 R 30)	RT-855	475	1544	682	4537	725	W16L	W14L W15L	50	1595	1860	2120	2380	2640	2900	---	---	---	---	---
									40	1595	1860	2120	2380	2640	2900	---	---	---	---	---
									30	1710	1990	2270	2550	2830	3105	---	---	---	---	---
									10 LT	2140	2490	2840	3190	3540	3890	---	---	---	---	---
									10 HT	1710	1990	2270	2550	2830	3105	---	---	---	---	---
320/85 R 32 126 A8 /B (Replaces 12.4 R 32)	RT-855	329	1357	621	4072	650	W11	W9 W10	50	935	1090	1245	1395	1550	1700	---	---	---	---	---
									40	935	1090	1245	1395	1550	1700	---	---	---	---	---
									30	1005	1165	1330	1495	1660	1820	---	---	---	---	---
									10 LT	1255	1460	1665	1870	2075	2280	---	---	---	---	---
									10 HT	1005	1165	1330	1495	1660	1820	---	---	---	---	---
320/85 R 34 141 A8 /B	RT-855	329	1458	645	4280	W11	----		50	930	1085	---	1420	---	1730	1880	2010	2190	2370	2575
									40	930	1085	---	1420	---	1730	1880	2010	2190	2370	2575
									30	995	1160	---	1520	---	1850	2015	2155	2350	2540	2760
									10 LT	1245	1455	---	1905	---	2315	2525	2695	2940	3180	3455
									10 HT	995	1160	---	1520	---	1850	2015	2155	2350	2540	2760
380/85 R 34 137 A8 /B (Replaces 14.9 R 34)	RT-855	380	1509	682	4461	725	W12	W11 W13	50	1265	1475	1680	1890	2095	2300	---	---	---	---	---
									40	1265	1475	1680	1890	2095	2300	---	---	---	---	---
									30	1360	1580	1800	2025	2245	2465	---	---	---	---	---
									10 LT	1700	1975	2255	2530	2810	3085	---	---	---	---	---
									10 HT	1360	1580	1800	2025	2245	2465	---	---	---	---	---
420/85 R 34 142 A8 /B (Replaces 16.9 R 34)	RT-855	438	1578	709	4677	750	W15L	W13 W14L	50	1460	1700	1935	2175	2415	2650	---	---	---	---	---
									40	1460	1700	1935	2175	2415	2650	---	---	---	---	---
									30	1565	1820	2075	2330	2585	2840	---	---	---	---	---
									10 LT	1960	2280	2600	2920	3240	3555	---	---	---	---	---
									10 HT	1565	1820	2075	2330	2585	2840	---	---	---	---	---
460/85 R 34 147 A8 /B (Replaces 18.4 R 34)	RT-855	475	1646	733	4845	775	W16L	W14L W15L	50	1695	1970	2245	2525	2800	3075	---	---	---	---	---
									40	1695	1970	2245	2525	2800	3075	---	---	---	---	---
									30	1815	2110	2410	2705	3000	3295	---	---	---	---	---
									10 LT	2270	2640	3015	3385	3755	4125	---	---	---	---	---
									10 HT	1815	2110	2410	2705	3000	3295	---	---	---	---	---
320/85 R 36 128 A8 /B (Replaces 12.4 R 36)	RT-855	329	1458	671	4357	700	W11	W9 W10	50	990	1155	1315	1480	1640	1800	---	---	---	---	---
									40	990	1155	1315	1480	1640	1800	---	---	---	---	---
									30	1065	1240	1410	1585	1760	1930	---	---	---	---	---
									10 LT	1330	1550	1765	1985	2200	2415	---	---	---	---	---
									10 HT	1065	1240	1410	1585	1760	1930	---	---	---	---	---

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
							REC.	ALT.												
Load capacity (kg / tyre)																				
340/85 R 36 132 A8 /B (Replaces 13.6 R 36)	RT-855	353	1492	687	4485	725	W12	W11	50	1100	1280	1460	1640	1820	2000	---	---	---	---	---
									40	1100	1280	1460	1640	1820	2000	---	---	---	---	---
									30	1180	1370	1565	1755	1950	2140	---	---	---	---	---
									10 LT	1475	1720	1960	2200	2440	2680	---	---	---	---	---
									10 HT	1180	1370	1565	1755	1950	2140	---	---	---	---	---
320/85 R 38 143 A8 /B	RT-855	319	1509	700	4580		W10	----	50	985	1145	---	1500	---	1830	1990	2130	2320	2510	2725
									40	985	1145	---	1500	---	1830	1990	2130	2320	2510	2725
									30	1055	1230	---	1610	---	1960	2135	2280	2485	2690	2920
									10 LT	1320	1540	---	2015	---	2450	2670	2855	3110	3365	3655
									10 HT	1055	1230	---	1610	---	1960	2135	2280	2485	2690	2920
340/85 R 38 133 A8 /B (Replaces 13.6 R 38)	RT-855	353	1543	712	4613	750	W12	W11	50	1135	1320	1505	1690	1875	2060	---	---	---	---	---
									40	1135	1320	1505	1690	1875	2060	---	---	---	---	---
									30	1215	1415	1610	1810	2010	2205	---	---	---	---	---
									10 LT	1525	1770	2020	2270	2520	2765	---	---	---	---	---
									10 HT	1215	1415	1610	1810	2010	2205	---	---	---	---	---
380/85 R 38 139 A8 /B (Replaces 14.9 R 38)	RT-855	380	1611	736	4800	775	W12	W11 W13	50	1340	1560	1775	1995	2215	2430	---	---	---	---	---
									40	1340	1560	1775	1995	2215	2430	---	---	---	---	---
									30	1435	1670	1905	2140	2375	2605	---	---	---	---	---
									10 LT	1795	2090	2380	2675	2970	3260	---	---	---	---	---
									10 HT	1435	1670	1905	2140	2375	2605	---	---	---	---	---
420/85 R 38 144 A8 /B (Replaces 16.9 R 38)	RT-855	438	1679	763	4992	800	W15L	W13 W14L	50	1540	1795	2045	2300	2550	2800	---	---	---	---	---
									40	1540	1795	2045	2300	2550	2800	---	---	---	---	---
									30	1650	1920	2190	2460	2730	3000	---	---	---	---	---
									10 LT	2070	2405	2745	3080	3420	3755	---	---	---	---	---
									10 HT	1650	1920	2190	2460	2730	3000	---	---	---	---	---
460/85 R 38 149 A8 /B (Replaces 18.4 R 38)	RT-855	475	1747	785	5161	825	W16L	W14L W15L	50	1790	2080	2375	2665	2960	3250	---	---	---	---	---
									40	1790	2080	2375	2665	2960	3250	---	---	---	---	---
									30	1915	2230	2545	2855	3170	3480	---	---	---	---	---
									10 LT	2400	2790	3180	3575	3965	4355	---	---	---	---	---
									10 HT	1915	2230	2545	2855	3170	3480	---	---	---	---	---
520/85 R 38 155 A8 /B (Replaces 20.8 R 38)	RT-855	516	1849	818	5416	875	DW16L	DW18L	50	2135	2480	2830	3180	3530	3875	---	---	---	---	---
									40	2135	2480	2830	3180	3530	3875	---	---	---	---	---
									30	2285	2660	3030	3405	3780	4150	---	---	---	---	---
									10 LT	2860	3325	3795	4260	4730	5195	---	---	---	---	---
									10 HT	2285	2660	3030	3405	3780	4150	---	---	---	---	---

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6							
							REC.	ALT.																			
Load capacity (kg / tyre)																											
520/85 R 38 HEAVY DUTY 170 A8 / 167 B (Replaces 20.8 R 38)	RT-855	540	1825	818	6450	875	DW16L	----	50	---	---	---	---	---	---	---	---	---	---	5450							
									40	---	---	---	---	---	---	---	---	---	---	---	---	---	---	6000			
									30	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	6420
									10 LT	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---
									10 HT	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---
480/80 R 42 151 A8 / B (Replaces 18.4 R 42)	RT-855	479	1835	835	5459	875	W16B	DW16B 16DD	50	1900	2210	2520	2830	3140	3450	---	---	---	---	---							
									40	1900	2210	2520	2830	3140	3450	---	---	---	---	---	---	---	---	---			
									30	2035	2365	2700	3030	3365	3695	---	---	---	---	---	---	---	---	---	---		
									10 LT	2545	2960	3380	3795	4210	4625	---	---	---	---	---	---	---	---	---	---		
									10 HT	2035	2365	2700	3030	3365	3695	---	---	---	---	---	---	---	---	---	---	---	
520/85 R 42 157 A8 / B (Replaces 20.8 R 42)	RT-855	516	1951	868	5710	925	DW16L	DW18L	50	2270	2640	3015	3385	3755	4125	---	---	---	---	---							
									40	2270	2640	3015	3385	3755	4125	---	---	---	---	---	---	---	---	---			
									30	2430	2830	3225	3625	4020	4415	---	---	---	---	---	---	---	---	---	---		
									10 LT	3045	3540	4040	4535	5035	5530	---	---	---	---	---	---	---	---	---	---		
									10 HT	2430	2830	3225	3625	4020	4415	---	---	---	---	---	---	---	---	---	---	---	
420/80 R 46 159 D / 170 A2	RT-855	418	1840	863	5619		W13		65	1625	1865	2140	2415	2695	2970	3210	3450	4070	4375	---							
									50	1705	1960	2250	2540	2830	3120	3375	3625	4275	4595	---							
									40	1780	2045	2345	2650	2950	3255	3520	3780	4460	4795	---							
									30	1870	2145	2465	2780	3100	3415	3695	3970	4685	5035	---							
									10	2235	2565	2945	3325	3705	4085	4420	4750	5580	6000	---							
									10 LT	2175	2500	2870	3240	3610	3980	4305	4625	5455	5865	---							
									10 HT	1870	2145	2465	2780	3100	3415	3695	3970	4685	5035	---							
480/80 R 46 158 A8 / B (Replaces 18.4 R 46)	RT-855	479	1936	885	5787	925	W16B	DW16B 16DD	50	2000	2295	2635	2975	3315	3655	3955	4250	---	---	---							
									40	2000	2295	2635	2975	3315	3655	3955	4250	---	---	---	---						
									30	2140	2460	2825	3185	3550	3915	4235	4550	---	---	---	---						
									10 LT	2680	3080	3535	3990	4445	4900	5300	5695	---	---	---	---						
									10 HT	2140	2460	2825	3185	3550	3915	4235	4550	---	---	---	---						
520/85 R 46 158 A8 / B (Replaces 20.8 R 46)	RT-855	516	2052	931	6115	975	DW16L	DW18L	50	2340	2720	3105	3485	3870	4250	---	---	---	---	---							
									40	2340	2720	3105	3485	3870	4250	---	---	---	---	---	---						
									30	2505	2915	3325	3735	4145	4550	---	---	---	---	---	---						
									10 LT	3135	3645	4160	4670	5185	5695	---	---	---	---	---	---						
									10 HT	2505	2915	3325	3735	4145	4550	---	---	---	---	---	---						

AGRIMAX RT-855 (85 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
							REC.	ALT.												
480/80 R 50 159 A8 /B (Replaces 18.4 R 50)	RT-855	479	2036	936	6108	975	W15ADW	----	50	2060	2365	2715	3065	3415	3765	4070	4375	---	---	---
									40	2060	2365	2715	3065	3415	3765	4070	4375	---	---	---
									30	2205	2530	2905	3280	3655	4030	4360	4685	---	---	---
									10 LT	2760	3170	3640	4110	4575	5045	5455	5865	---	---	---
									10 HT	2205	2530	2905	3280	3655	4030	4360	4685	---	---	---

SW - On the first Rim of the list.

50/40/30 = On Road transport at 50/40/30 km/h.

10 LT = Maximum speed 10 km/h. Surface treatment with low torque value.

10 HT = Maximum speed 10 km/h. Field application with high torque value.

For dual mounting use, per each wheel, the 88% of loading indicated for single mounting.

* All tyres conform to ETRTO standards.

S = Single fitment.

SRI = Speed Radius index - value to be used for the calculation of the theoretical tractor speed during European Union homologation and for the interchangeability of different type sizes.