

## Tractor Front Tyres (F-2 & F3)

Tyre Size	Pattern	Rim		Unloaded inflated Dimensions		Static Loaded Radius (mm)	Rolling Circumference ± 2.5 % (mm)	Ply Rating	Type	Load capacity				Inflation Pressure (bar)
				± 2 %						30 km/h		40 km/h		
		Rec.	Alt.	Section Width (mm)	Overall Diameter (mm)					A6 Load Index	Max. Load (kgs)	A8 Load Index	Max. Load (kgs)	
4.00 - 12	TF-9090	3.00 D	2.50 C	112	530			4	TT	60	250	52	200	3.4
								6	tt	68	315	60	250	5.1
5.00 - 15	TF-9090	4.00 E	3.00 D, 4J, 4 ½ J	140	655	307	1951	4	TT	73	365	65	290	2.8
5.50 - 16	TF-9090	4.00 E	3.50 D, 4.50 E	150	710	332	2116	6	TT	86	530	78	425	3.7
6.00 - 16	TF-9090	4.50 E	5.00 F	170	735	346	2190	6	TT	88	560	80	450	3.3
								8	TT	94	670	87	545	4.5
6.50 - 16	TF-9090	4.50 E	4.00 E, 5 K, 5.00 F, 5.50 F	180	765	359	2280	6	TT	91	615	83	487	3.1
								8	TT	98	750	90	600	4.2
7.50 - 16	TF-9090	5.50 F	6.00 F	207	810	379	2414	6	TT	98	750	90	600	2.8
								8	TT	103	875	96	710	3.7
								10	TT	109	1030	101	825	4.8
9.00 - 16	TF-9090	W 8	6.00 F, W 7, W 8 L	237	855	398	2548	8	TT	111	1090	103	875	3.1
								10	TT	116	1250	108	1000	3.9
10.00 - 16	TF-9090	W 8	W8 L	275	900	418	2682	8	TT	115	1215	107	975	2.8
								10	TT	119	1360	111	1090	3.4
11.00 - 16	TF-9090	W 10 L	W 8, W 8L	320	970	448	2890	8	TT	118	1320	110	1060	2.5
7.50 - 18	TF-9090	5.50 F	---	207	860	404	2562	6	TT	101	825	94	670	2.8
								8	TT	106	950	98	750	3.7
4.00 - 19	TF-9090	3.00 D	---	115	715	343	2145	4	TT	72	355	64	280	3.4
6.00 - 19	TF-9090	4.50 E	5.00 F	167	815	386	2445	6	TT	93	650	85	515	3.3
7.50 - 20	TF-9090	5.50 F	5.00 F	205	915	431	2725	6	TT	103	875	96	710	2.8
								8	TT	108	1000	101	825	3.4

All tyres conform to ETRTO standards