

AGRIMAX RT-765 (70 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	2.90	
							REC.	ALT.												
										Load capacity (kg / tyre)										
200/70 R 16 94 A8 /B	RT-765	197	686	313	2058	330	W6	---	50	315	365	420	470	525	580	625	670	---	---	
									40	315	365	420	470	525	580	625	670	---	---	
									30	340	390	450	505	565	620	670	720	---	---	
									10 LT	425	490	560	630	705	775	840	900	---	---	
									10 HT	340	390	450	505	565	620	670	720	---	---	
220/70 R 16 97 A8 /B	RT-765	221	715	324	2145		W7	---	50	315	365	420	470	525	580	625	670	---	---	
									40	315	365	420	470	525	580	625	670	---	---	
									30	340	390	450	505	565	620	670	720	---	---	
									10 LT	425	490	560	630	705	775	840	900	---	---	
									10 HT	340	390	450	505	565	620	670	720	---	---	
240/70 R 16 104 A8 /B	RT-765	244	742	335	2226	350	W8	W8L W9	50	425	490	560	630	705	775	840	900	900	---	---
									40	425	490	560	630	705	775	840	900	---	---	
									30	455	525	600	680	755	830	900	965	---	---	
									10 LT	570	655	755	850	945	1045	1130	1210	---	---	
									10 HT	455	525	600	680	755	830	900	965	---	---	
260/70 R 16 109 A8 /B	RT-765	258	770	346	2310	360	W8	W8L W9	50	485	560	640	725	805	890	960	1030	---	---	
									40	485	560	640	725	805	890	960	1030	---	---	
									30	520	600	690	775	865	955	1030	1105	---	---	
									10 LT	650	750	860	970	1080	1190	1285	1380	---	---	
									10 HT	520	600	690	775	865	955	1030	1105	---	---	
280/70 R 16 112 A8 /B	RT-765	282	798	356	2370	390	W9	W8L W10	50	530	605	695	785	875	965	1045	1120	---	---	
									40	530	605	695	785	875	965	1045	1120	---	---	
									30	565	650	745	840	940	1035	1120	1200	---	---	
									10 LT	710	815	935	1055	1175	1295	1400	1505	---	---	
									10 HT	565	650	745	840	940	1035	1120	1200	---	---	
280/70 R 18 114 A8 /B	RT-765	282	849	381	2520	410	W9	W8 W10	50	555	640	735	830	925	1015	1100	1180	---	---	
									40	555	640	735	830	925	1015	1100	1180	---	---	
									30	595	685	785	890	990	1090	1180	1265	---	---	
									10 LT	745	860	985	1110	1240	1365	1475	1585	---	---	
									10 HT	595	685	785	890	990	1090	1180	1265	---	---	
260/70 R 20 113 A8 /B	RT-765	258	872	400	2643	410	W8	W9	50	545	625	715	805	900	990	1070	1150	---	---	
									40	545	625	715	805	900	990	1070	1150	---	---	
									30	585	670	770	865	965	1065	1150	1235	---	---	
									10 LT	730	835	960	1085	1210	1330	1440	1545	---	---	
									10 HT	585	670	770	865	965	1065	1150	1235	---	---	
280/70 R 20 116 A8 /B	RT-765	282	900	408	2703	425	W9	W10	50	590	675	775	875	975	1075	1165	1250	---	---	
									40	590	675	775	875	975	1075	1165	1250	---	---	
									30	630	725	835	940	1050	1155	1250	1340	---	---	
									10 LT	790	905	1040	1175	1310	1445	1560	1675	---	---	
									10 HT	630	725	835	940	1050	1155	1250	1340	---	---	

AGRIMAX RT-765 (70 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	2.90
							REC.	ALT.											
										Load capacity (kg / tyre)									
300/70 R 20 120 A8 /B	RT-765	295	952	427	2850	450	W9	W10	50	660	760	870	980	1095	1205	1305	1400	---	---
									40	660	760	870	980	1095	1205	1305	1400	---	---
									30	705	810	930	1050	1170	1290	1395	1500	---	---
									10 LT	885	1020	1170	1320	1470	1620	1750	1880	---	---
									10 HT	705	810	930	1050	1170	1290	1395	1500	---	---
320/70 R 20 123 A8 /B	RT-765	319	982	440	2940	475	W10	W9 W11	50	730	840	965	1085	1210	1335	1445	1550	---	---
									40	730	840	965	1085	1210	1335	1445	1550	---	---
									30	785	900	1030	1165	1295	1430	1545	1660	---	---
									10 LT	980	1125	1290	1460	1625	1790	1935	2080	---	---
									10 HT	785	900	1030	1165	1295	1430	1545	1660	---	---
360/70 R 20 129 A8 /B	RT-765	357	1042	465	3150	500	W11	W10 W12	50	870	1000	1150	1295	1445	1595	1725	1850	---	---
									40	870	1000	1150	1295	1445	1595	1725	1850	---	---
									30	935	1070	1230	1390	1545	1705	1845	1980	---	---
									10 LT	1170	1340	1540	1740	1935	2135	2310	2480	---	---
									10 HT	935	1070	1230	1390	1545	1705	1845	1980	---	---
380/70 R 20 132 A8 /B	RT-765	380	1082	479	3240	525	W12	W11 W13	50	940	1080	1240	1400	1560	1720	1860	2000	---	---
									40	940	1080	1240	1400	1560	1720	1860	2000	---	---
									30	1010	1160	1330	1500	1670	1845	1995	2140	---	---
									10 LT	1260	1450	1665	1880	2095	2305	2495	2680	---	---
									10 HT	1010	1160	1330	1500	1670	1845	1995	2140	---	---
320/70 R 24 116 A8 /B	RT-765	319	1094	499	3290	525	W10	W9 W11	50	690	800	915	1025	1140	1250	---	---	---	---
									40	690	800	915	1025	1140	1250	---	---	---	---
									30	740	860	980	1100	1220	1340	---	---	---	---
									10 LT	925	1075	1225	1375	1525	1675	---	---	---	---
									10 HT	740	860	980	1100	1220	1340	---	---	---	---
360/70 R 24 122 A8 /B	RT-765	357	1152	519	3455	550	W11	W10 W12	50	825	960	1095	1230	1365	1500	---	---	---	---
									40	825	960	1095	1230	1365	1500	---	---	---	---
									30	885	1030	1175	1320	1465	1605	---	---	---	---
									10 LT	1110	1290	1470	1650	1830	2010	---	---	---	---
									10 HT	885	1030	1175	1320	1465	1605	---	---	---	---
380/70 R 24 125 A8 /B	RT-765	380	1190	533	3534	575	W12	W11 W13	50	910	1060	1205	1355	1505	1650	---	---	---	---
									40	910	1060	1205	1355	1505	1650	---	---	---	---
									30	975	1135	1295	1455	1615	1770	---	---	---	---
									10 LT	1220	1420	1620	1820	2020	2215	---	---	---	---
									10 HT	975	1135	1295	1455	1615	1770	---	---	---	---
420/70 R 24 130 A8 /B	RT-765	418	1248	554	3694	600	W13	W12 W14L	50	1045	1220	1390	1560	1730	1900	---	---	---	---
									40	1045	1220	1390	1560	1730	1900	---	---	---	---
									30	1120	1305	1490	1670	1855	2035	---	---	---	---
									10 LT	1405	1635	1865	2095	2325	2550	---	---	---	---
									10 HT	1120	1305	1490	1670	1855	2035	---	---	---	---

AGRIMAX RT-765 (70 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	2.90
							REC.	ALT.											
480/70 R 24 138 A8 /B	RT-765	479	1316	580	3894	625	W15L	W14L W16L	50	1300	1515	1725	1940	2150	2360	---	---	---	---
									40	1300	1515	1725	1940	2150	2360	---	---	---	---
									30	1390	1620	1845	2075	2300	2525	---	---	---	---
									10 LT	1740	2025	2310	2595	2880	3162	---	---	---	---
									10 HT	1390	1620	1845	2075	2300	2525	---	---	---	---
360/70 R 28 125 A8 /B	RT-765	357	1251	571	3767	600	W11	W10 W12	50	910	1060	1205	1355	1505	1650	---	---	---	---
									40	910	1060	1205	1355	1505	1650	---	---	---	---
									30	975	1135	1295	1455	1615	1770	---	---	---	---
									10 LT	1220	1420	1620	1820	2020	2215	---	---	---	---
									10 HT	975	1135	1295	1455	1615	1770	---	---	---	---
380/70 R 28 127 A8 /B	RT-765	380	1293	584	3861	625	W12	W11 W13	50	965	1120	1280	1435	1595	1750	---	---	---	---
									40	965	1120	1280	1435	1595	1750	---	---	---	---
									30	1035	1200	1370	1540	1710	1875	---	---	---	---
									10 LT	1290	1505	1715	1925	2135	2345	---	---	---	---
									10 HT	1035	1200	1370	1540	1710	1875	---	---	---	---
420/70 R 28 133 A8 /B	RT-765	418	1349	604	3993	650	W13	W12 W14L	50	1135	1320	1505	1690	1875	2060	---	---	---	---
									40	1135	1320	1505	1690	1875	2060	---	---	---	---
									30	1215	1415	1610	1810	2010	2205	---	---	---	---
									10 LT	1525	1770	2020	2270	2520	2765	---	---	---	---
									10 HT	1215	1415	1610	1810	2010	2205	---	---	---	---
480/70 R 28 140 A8 /B	RT-765	479	1421	634	4217	675	W15L	W14L W16L	50	1375	1600	1825	2050	2275	2500	---	---	---	---
									40	1375	1600	1825	2050	2275	2500	---	---	---	---
									30	1475	1715	1955	2195	2435	2675	---	---	---	---
									10 LT	1845	2145	2450	2750	3050	3350	---	---	---	---
									10 HT	1475	1715	1955	2195	2435	2675	---	---	---	---
420/70 R 30 134 A8 /B	RT-765	418	1398	631	4172	675	W13	W12 W14L	50	1170	1360	1550	1740	1930	2120	---	---	---	---
									40	1170	1360	1550	1740	1930	2120	---	---	---	---
									30	1250	1455	1660	1865	2070	2270	---	---	---	---
									10 LT	1565	1825	2080	2335	2590	2845	---	---	---	---
									10 HT	1250	1455	1660	1865	2070	2270	---	---	---	---
480/70 R 30 141 A8 /B	RT-765	479	1478	659	4370	700	W15L	W14L W16L	50	1420	1650	1880	2115	2345	2575	---	---	---	---
									40	1420	1650	1880	2115	2345	2575	---	---	---	---
									30	1520	1770	2015	2265	2515	2760	---	---	---	---
									10 LT	1905	2215	2525	2835	3145	3455	---	---	---	---
									10 HT	1520	1770	2015	2265	2515	2760	---	---	---	---
600/70 R 30 152 A8 /B	RT-765	591	1602	711	4774	750	DW20B DW18L	W18L	50	1955	2275	2595	2915	3235	3550	---	---	---	---
									40	1955	2275	2595	2915	3235	3550	---	---	---	---
									30	2090	2435	2775	3120	3460	3800	---	---	---	---
									10 LT	2620	3050	3475	3905	4335	4760	---	---	---	---
									10 HT	2090	2435	2775	3120	3460	3800	---	---	---	---

AGRIMAX RT-765 (70 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	2.90	
							REC.	ALT.												
Load capacity (kg / tyre)																				
480/70 R 34 149 A8 /B	RT-765	479	1580	711	4740	750	W15L	W14L	50	1530	1755	2015	2275	2535	2795	3025	3250	---	---	
									40	1530	1755	2015	2275	2535	2795	3025	3250	---	---	
									W16L	30	1640	1880	2160	2440	2715	2995	3240	3480	---	---
										10 LT	2050	2355	2705	3050	3400	3750	4055	4355	---	---
										10 HT	1640	1880	2160	2440	2715	2995	3240	3480	---	---
520/70 R 34 148 A8 /B	RT-765	516	1640	738	4914	775	W16L	W15L	50	1735	2020	2300	2585	2870	3150	---	---	---	---	
									40	1735	2020	2300	2585	2870	3150	---	---	---	---	
									W18L	30	1860	2160	2465	2770	3075	3375	---	---	---	---
										10 LT	2325	2705	3085	3465	3845	4225	---	---	---	---
										10HT	1860	2160	2465	2770	3075	3375	---	---	---	---
480/70 R 38 145 A8 /B	RT-765	479	1681	764	4995	800	W15L	W14L	50	1595	1860	2120	2380	2640	2900	---	---	---	---	
									40	1595	1860	2120	2380	2640	2900	---	---	---	---	
									W16L	30	1710	1990	2270	2550	2830	3105	---	---	---	---
										10 LT	2140	2490	2840	3190	3540	3890	---	---	---	---
										10 HT	1710	1990	2270	2550	2830	3105	---	---	---	---
520/70 R 38 150 A8 /B	RT-765	516	1749	793	5235	825	W16L	W15L	50	1845	2145	2450	2750	3050	3350	---	---	---	---	
									40	1845	2145	2450	2750	3050	3350	---	---	---	---	
									W18L	30	1975	2295	2620	2940	3265	3585	---	---	---	---
										10 LT	2470	2875	3280	3685	4090	4490	---	---	---	---
										10 HT	1975	2295	2620	2940	3265	3585	---	---	---	---
580/70 R 38 155 A8 /B	RT-765	577	1827	821	5443	875	W18L	---	50	2135	2480	2830	3180	3530	3875	---	---	---	---	
									40	2135	2480	2830	3180	3530	3875	---	---	---	---	
									30	2285	2660	3030	3405	3780	4150	---	---	---	---	
									10 LT	2860	3325	3795	4260	4730	5195	---	---	---	---	
									10 HT	2285	2660	3030	3405	3780	4150	---	---	---	---	
710/70 R 38 166 A8 /B	RT-765	716	1959	859	5751	925	DW23A	---	50	2915	3395	3870	4350	4825	5300	---	---	---	---	
									40	2915	3395	3870	4350	4825	5300	---	---	---	---	
									---	30	3125	3635	4145	4655	5165	5675	---	---	---	---
										10 LT	3910	4550	5190	5830	6470	7105	---	---	---	---
										10 HT	3125	3635	4145	4655	5165	5675	---	---	---	---
710/70 R 38 178 A8 /175 B	RT-765	716	1959	859	5751	925	DW23A	---	50	2915	3395	3870	4350	4825	5300	5550	6175	6760	6900	
									40	2915	3395	3870	4350	4825	5300	6035	6720	7350	7500	
									30	3125	3635	4145	4655	5165	5675	6460	7195	7865	8025	
									10 LT	3910	4550	5190	5830	6470	7105	8090	9005	9850	10050	
									10 HT	3125	3635	4145	4655	5165	5675	6460	7195	7865	8025	
620/70 R 42 160 A8 /B	RT-765	625	1935	866	5692	925	DW20A	---	50	2475	2880	3285	3690	4095	4500	---	---	---	---	
									40	2475	2880	3285	3690	4095	4500	---	---	---	---	
									---	30	2650	3085	3515	3950	4385	4815	---	---	---	---
										10 LT	3320	3860	4405	4945	5490	6030	---	---	---	---
										10 HT	2650	3085	3515	3950	4385	4815	---	---	---	---

AGRIMAX RT-765 (70 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	2.90
							REC.	ALT.											
710/70 R 42 173 A8 /B	RT-765	716	2061	922	6174	975	DW23A	---	50	3055	3510	4030	4550	5070	5590	6045	6500	---	---
									40	3055	3510	4030	4550	5070	5590	6045	6500	---	---
									30	3270	3760	4315	4870	5425	5985	6470	6955	---	---
									10 LT	4095	4705	5405	6100	6795	7495	8105	8710	---	---
									10 HT	3270	3760	4315	4870	5425	5985	6470	6955	---	---
710/70 R 42 173 D /176 A8	RT-765	716	2061	922	6174	975	DW23A	---	65	3120	3640	4095	4550	5005	5395	5980	6500	---	---
									50	3280	3825	4300	4780	5260	5665	6280	6825	---	---
									40	3410	3980	4475	4970	5470	5895	6535	7100	---	---
									30	3590	4190	4710	5235	5760	6205	6880	7475	---	---
									10 LT	4185	4880	5490	6100	6710	7230	8015	8710	---	---
10 HT	3590	4190	4710	5235	5760	6205	6880	7475	---	---									
620/70 R 46 162 A8 /B	RT-765	625	2036	920	6036	975	DW20B	---	50	2615	3040	3470	3895	4325	4750	---	---	---	---
									40	2615	3040	3470	3895	4325	4750	---	---	---	---
									30	2800	3255	3715	4170	4630	5085	---	---	---	---
									10 LT	3505	4075	4650	5220	5795	6365	---	---	---	---
									10 HT	2800	3255	3715	4170	4630	5085	---	---	---	---

AGRIMAX RT-765 (70 Series) - Tractor Radial Tyres (Steel Belted)

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	3.20	3.60	4.00	4.40	4.60
							REC.	ALT.															
580/70 R 38 STEEL BELTED 180A8	RT-765	577	1827	827	5550	875	W18L	---	50	2135	2480	2830	3180	3530	3875	4490	4990	5460	5890	6310	6710	7090	7280
									40	2135	2480	2830	3180	3530	3875	4930	5480	6000	6470	6930	7370	7790	8000
									30	2285	2660	3030	3405	3780	4150	5280	5860	6420	6920	7420	7890	8340	8560
									25	2370	2760	3145	3535	3920	4305	5470	6080	6660	7180	7690	8180	8650	8880

<p>SW - On the first Rim of the list. 50/40/30 = On Road transport at 50/40/30 km/h. 10 LT = Maximum speed 10 km/h. Surface treatment with low torque value. 10 HT = Maximum speed 10 km/h. Field application with high torque value.</p> <p>For dual mounting use, per each wheel, the 88% of loading indicated for single mounting.</p>	<p>* All tyres conform to ETRTO standards. S = Single fitment. SRI = Speed Radius index - value to be used for the calculation of the theoretical tractor speed during European Union homologation and for the interchangeability of different type sizes.</p>
--	--