

## AGRIMAX RT-955 (Row Crop 95 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.80	1.20	1.60	2.00	2.40	2.80	3.20	3.60	4.00	4.40
							REC.	ALT.											
<b>230/95 R 32</b> <b>128 A8 /B</b> (Replaces 9.5 R 32)	RT-955	238	1251	578	3753	625	<b>W8</b>	W7	50	705	920	1120	1225	1300	1425	1550	1675	1800	---
									40	705	920	1120	1225	1300	1425	1550	1675	1800	---
									30	755	985	1200	1315	1390	1525	1660	1795	1930	---
									10	840	1055	1300	1540	1785	1840	2055	2270	2485	2700
<b>270/95 R 32</b> <b>136 A8 /B</b> (Replaces 11.2 R 32)	RT-955	265	1327	611	4011	625	<b>W8</b>	W9 W10	50	875	1145	1390	1525	1615	1770	1930	2085	2240	---
									40	875	1145	1390	1525	1615	1770	1930	2085	2240	---
									30	940	1225	1490	1635	1730	1900	2065	2235	2400	---
									10	1045	1315	1615	1920	2220	2285	2555	2825	3095	3360
<b>230/95 R 36</b> <b>130 A8 /B</b> (Replaces 9.5 R 36)	RT-955	238	1352	620	4056	650	<b>W8</b>	W7	50	745	970	1180	1295	1370	1505	1635	1770	1900	---
									40	745	970	1180	1295	1370	1505	1635	1770	1900	---
									30	795	1040	1265	1385	1470	1610	1755	1895	2035	---
									10	885	1115	1370	1625	1885	1940	2170	2395	2625	2850
<b>270/95 R 36</b> <b>139 A8 /B</b> (Replaces 11.2 R 36)	RT-955	265	1428	661	4315	675	<b>W8</b>	W9 W10	50	950	1240	1510	1655	1750	1920	2090	2260	2430	---
									40	950	1240	1510	1655	1750	1920	2090	2260	2430	---
									30	1020	1330	1620	1775	1880	2060	2245	2425	2605	---
									10	1130	1425	1750	2080	2410	2480	2775	3065	3355	3645
<b>270/95 R 38</b> <b>140 A8 /B</b> (Replaces 11.2 R 38)	RT-955	265	1479	684	4437	700	<b>W8</b>	W9 W10	50	975	1275	1550	1700	1800	1975	2150	2325	2500	---
									40	975	1275	1550	1700	1800	1975	2150	2325	2500	---
									30	1045	1365	1660	1820	1930	2115	2305	2490	2675	---
									10	1165	1465	1800	2140	2475	2550	2850	3150	3450	3750
<b>230/95 R 42</b> <b>133 A8 /B</b> (Replaces 9.5 R 42)	RT-955	238	1506	706	4518	725	<b>W8</b>	W7	50	805	1055	1280	1405	1485	1630	1775	1920	2060	---
									40	805	1055	1280	1405	1485	1630	1775	1920	2060	---
									30	860	1125	1370	1500	1590	1745	1900	2055	2205	---
									10	960	1210	1485	1765	2040	2105	2350	2600	2845	3090
<b>230/95 R 44</b> <b>134 A8 /B</b> (Replaces 9.5 R 44)	RT-955	238	1556	733	4700	750	<b>W8</b>	W7	50	830	1085	1315	1445	1530	1675	1825	1975	2120	---
									40	830	1085	1315	1445	1530	1675	1825	1975	2120	---
									30	890	1160	1410	1545	1635	1795	1955	2115	2270	---
									10	990	1245	1530	1815	2100	2165	2420	2675	2930	3180
<b>270/95 R 44</b> <b>142 A8 /B</b> (Replaces 11.2 R 44)	RT-955	265	1632	761	4896	775	<b>W8</b>	W9 W10	50	1035	1355	1645	1805	1910	2095	2280	2465	2650	---
									40	1035	1355	1645	1805	1910	2095	2280	2465	2650	---
									30	1110	1450	1765	1935	2045	2245	2445	2645	2840	---
									10	1235	1555	1910	2270	2625	2705	3025	3340	3660	3975

## AGRIMAX RT-955 (Row Crop 95 Series) - Tractor Radial Tyres

SIZE	PATTERN	S.W (mm)	O.D (mm)	SLR (mm)	RC (mm)	SRI (mm)	RIM		bar km/h	0.80	1.20	1.60	2.00	2.40	2.80	3.20	3.60	4.00	4.40
							REC.	ALT.											
Load capacity (kg /tyre)																			
<b>300/95 R 46</b> <b>148 A8 /B</b> (Replaces 12.4 R 46)	RT-955	305	1738	807	5205	825	<b>W10</b>	W9 W11	50	1230	1610	1955	2145	2270	2490	2710	2930	3150	---
									40	1230	1610	1955	2145	2270	2490	2710	2930	3150	---
									30	1320	1725	2095	2295	2430	2670	2905	3140	3375	---
									10	1465	1845	2270	2695	3120	3215	3595	3970	4350	4725
<b>230/95 R 48</b> <b>136 A8 /B</b> (Replaces 9.5 R 48)	RT-955	238	1656	783	4980	800	<b>W8</b>	W7	50	875	1145	1390	1525	1615	1770	1930	2085	2240	---
									40	875	1145	1390	1525	1615	1770	1930	2085	2240	---
									30	940	1225	1490	1635	1730	1900	2065	2235	2400	---
									10	1045	1315	1615	1920	2220	2285	2555	2825	3095	3360
<b>270/95 R 48</b> <b>144 A8 /B</b> (Replaces 11.2 R 48)	RT-955	265	1733	816	5252	825	<b>W8</b>	W9 W10	50	1095	1430	1740	1905	2020	2215	2410	2605	2800	---
									40	1095	1430	1740	1905	2020	2215	2410	2605	2800	---
									30	1170	1530	1860	2040	2160	2370	2580	2790	3000	---
									10	1305	1640	2020	2395	2775	2860	3195	3530	3865	4200
<b>340/85 R 48</b> <b>152 A8 /B</b> (Replaces 13.6 R 48)	RT-955	353	1797	836	5391	875	<b>W12</b>	W11	50	1385	1815	2205	2415	2560	2805	3055	3305	3550	---
									40	1385	1815	2205	2415	2560	2805	3055	3305	3550	---
									30	1485	1940	2360	2585	2740	3005	3270	3535	3800	---
									10	1655	2080	2560	3040	3515	3625	4050	4475	4900	5325
<b>300/95 R 52</b> <b>151 A8 /B</b> (Replaces 12.4 R 52)	RT-955	305	1891	884	5673	925	<b>W10</b>	W9 W11	50	1350	1760	2140	2350	2485	2730	2970	3210	3450	---
									40	1350	1760	2140	2350	2485	2730	2970	3210	3450	---
									30	1445	1885	2295	2515	2665	2920	3180	3440	3695	---
									10	1605	2020	2485	2950	3420	3520	3935	4350	4765	5175
<b>270/95 R 54</b> <b>146 A8 /B</b> (Replaces 11.2 R 54)	RT-955	265	1885	887	5655	925	<b>W8</b>	W9,W10	50	1170	1530	1860	2040	2160	2370	2580	2790	3000	---
									40	1170	1530	1860	2040	2160	2370	2580	2790	3000	---
									30	1255	1640	1995	2185	2315	2540	2765	2990	3210	---
									10	1395	1755	2160	2565	2970	3060	3420	3780	4140	4500

SW - On the first Rim of the list.  
 50/40/30 = On Road transport at 50/40/30 km/h.  
 10 = Maximum speed 10 km/h. Field application.

For dual mounting use, per each wheel, the 88% of loading indicated for single mounting.

\* All tyres conform to ETRTO standards.

S = Single fitment.

SRI = Speed Radius index - value to be used for the calculation of the theoretical tractor speed during European Union homologation and for the interchangeability of different type sizes.